

Printing date 15.12.2022 Version number 2 Revision: 01.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Original ATE Brake Fluid SUPER DOT 5.1

Article number: 03.9901-66xx.x/7066xx

UFI: 6C00-60K6-500P-G4K8

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture hydraulic liquid

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Continental Aftermarket & Services GmbH

Sodener Straße 9

D-65824 Schwalbach am Taunus

Tel: +49-6196-87-0

Further information obtainable from:

Gefahrstoffmanagement Konzern. Zentrales Materiallabor

ate.sicherheit@contiautomotive.com

1.4 Emergency telephone number:

National Poisons Information Centre: +353 (1) 809 2166 (8.00 a.m. to 10.00 p.m. 7 days a week).

Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified according to the CLP regulation.

Hazard pictograms GHS08

Signal word Warning

Hazard-determining components of labelling:

Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate

Hazard statements

H361d Suspected of damaging the unborn child.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.
P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

ΙE



Printing date 15.12.2022 Version number 2 Revision: 01.12.2022

Trade name: Original ATE Brake Fluid SUPER DOT 5.1

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

•		
Dangerous components:		
CAS: 30989-05-0 EINECS: 250-418-4 Reg.nr.: 01-2119462824-33- XXXX	Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate Repr. 2, H361d	<70%
EC number: 907-996-4 Reg.nr.: 01-2119531322-53- XXXX 01-2119475115-41- XXXX 01-2119475107-38	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Eye Dam. 1, H318 Specific concentration limits: Eye Dam. 1; H318: C ≥ 30 % Eye Irrit. 2; H319: 20 % ≤ C < 30 %	<15%
CAS: 110-97-4 EINECS: 203-820-9 Reg.nr.: 01-21194754444-34- XXXX	1,1'-iminodipropan-2-ol Eye Irrit. 2, H319	<2%
CAS: 111-46-6 EINECS: 203-872-2 Reg.nr.: 01-2119457857-21	2,2'-oxybisethanol Acute Tox. 4, H302	<2%
CAS: 111-77-3 EINECS: 203-906-6 Reg.nr.: 01-2119475100-52- XXXX	2-(2-methoxyethoxy)ethanol Repr. 2, H361d	<0.5%

SVHC

Does not contain any or < 0,1% SVHC according to Regulation (EC) No 1907/2006 (REACH),

Article 57.

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Remove contaminated clothes and shoes immediately.

After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation. **After skin contact:** Immediately wash with water and soap and rinse thoroughly. **After eye contact:** Rinse opened eye for several minutes under running water.

After swallowing:

Rinse out mouth and then drink plenty of water.

Seek medical treatment.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Water spray

Fire-extinguishing powder

Foam

(Contd. on page 3)



Printing date 15.12.2022 Version number 2 Revision: 01.12.2022

Trade name: Original ATE Brake Fluid SUPER DOT 5.1

(Contd. of page 2)

Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture

May be released in case of fire: CO, CO2, NOx

5.3 Advice for firefighters Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

6.2 Environmental precautions: Do not allow to enter sewers/surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. **Information about fire - and explosion protection:** Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store cool and dry.

Storage at room temperature.

Information about storage in one common storage facility:

Store away from water.

Store away from foodstuffs.

Further information about storage conditions:

Recommended storage temperature: 10°C - 35°C.

This product is hygroscopic.

Store in dry conditions.

Keep container tightly sealed.

Storage class according to TRGS 510: 10 combustible liquids.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

111-46-6 2,2'-oxybisethanol

OEL Long-term value: 100 mg/m³, 23 ppm

111-77-3 2-(2-methoxyethoxy)ethanol

OEL Long-term value: 50.1 mg/m³, 10 ppm Sk, IOELV

(Contd. on page 4)



Version number 2 Revision: 01.12.2022 Printing date 15.12.2022

Trade name: Original ATE Brake Fluid SUPER DOT 5.1

(Contd. of page 3)

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Respiratory protection:

Respiratory protection required in case of release of vapors / aerosols.

Use particulate filter with medium retention capacity for solid and liquid particles (eg EN 143 or 149, type P2 or FFP2).

Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

Butyl caoutchouc (butyl rubber): minimum breakthrough time 480 min; minimum layer thickness: 0.7

NBR (nitrile rubber): minimum breakthrough time 30 min; minimum layer thickness: 0.4 mm The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Safety glasses

Body protection: Protective work clothing

Environmental exposure controls See section 6 and 7. No additional measures necessary.

Risk management measures

Use at industrial site in closed process with occasional controlled exposure or processes with equivalent containment conditions:

1 to 3 air changes per hour (90 % effectiveness) - basic standard of general ventilation maximum 8 h exposure duration per day maximum 40 °C process temperature

Use of functional fluids in small devices:

5 to 10 air changes per hour (70 % effectiveness) - good standard of controlled ventilation maximum 8 h exposure duration per day maximum 40 °C process temperature

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Colour: Amber coloured Odour: Product specific Odour threshold: Not determined. Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and

boiling range 271 °C (ASTM D1120) Flammability Not applicable.

Lower and upper explosion limit

Lower: Not determined. Upper: Not determined.

Flash point: 137.5 °C (DIN EN 22719; ISO 2719)

Ignition temperature: 230 °C (DIN 51794) **Decomposition temperature:** Not determined.

(Contd. on page 5)

(Contd. of page 4)



Safety data sheet according to 1907/2006/EC, Article 31

Version number 2 Revision: 01.12.2022 Printing date 15.12.2022

Trade name: Original ATE Brake Fluid SUPER DOT 5.1

7.7 (50 %(m))

pH at 20 °C

Viscosity:

Kinematic viscosity at 23 °C 11.5 mm²/s (ASTM D445)

Not determined. Dynamic: Fully miscible. water:

Partition coefficient n-octanol/water (log

value) Not determined.

Vapour pressure at 20 °C: 1 hPa

Density and/or relative density

Density at 20 °C: 1.06 g/cm³ (DIN 51757)

Relative density Not determined. Vapour density Not determined.

9.2 Other information No further relevant information available.

Appearance:

Form: Fluid

Important information on protection of health

and environment, and on safety.

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

Void

Void

Change in condition

Evaporation rate Not determined.

Information with regard to physical hazard

classes **Explosives** Void Flammable gases Void **Aerosols** Void Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void **Oxidising liquids** Void Oxidising solids Void Organic peroxides Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Corrosive to metals

Desensitised explosives

Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: Strong oxidizing agents

10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

(Contd. on page 6)



Printing date 15.12.2022 Version number 2 Revision: 01.12.2022

Trade name: Original ATE Brake Fluid SUPER DOT 5.1

Nitrogen oxides (NOx)

(Contd. of page 5)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

Acute	Acute toxicity based on available data, the classification chiefla are not met.				
LD/LC5	0 valu	es relevant for classification:			
30989-0	5-0 Tr	is[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate			
Oral	LD50	>2,000 mg/kg (rat) (OECD 401)			
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)			
Reactio	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol				
Oral	LD50	>5,000 mg/kg (rat)			
Dermal	LD50	>3,000 mg/kg (rabbit)			
110-97-	110-97-4 1,1'-iminodipropan-2-ol				
Oral	LD50	>2,000 mg/kg (rat) (OECD 401)			
Dermal	LD50	8,000 mg/kg (rabbit)			
111-46-	111-46-6 2,2'-oxybisethanol				
Oral	LD50	>5,000 mg/kg (rat)			
Dermal	LD50	>5,000 mg/kg (rabbit)			
111-77-	3 2-(2-	methoxyethoxy)ethanol			
Oral	LD50	>5,000 mg/kg (mouse) (OECD 401)			
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)			

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eve damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients are listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic t	oxicity:
LC50	>100 mg/L (fish)
30989-05	i-0 Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate
EC50	>100 mg/l (Algae) (72 h)
	>100 mg/l (daphnia) (48 h)
LC50	>100 mg/L (fish) (96 h)
Reaction	mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol
EC50	>100 mg/l (Algae)
LC50	>100 mg/L (daphnia)
	>100 mg/L (fish) (DIN 38412 96 h)
	(Contd. on page 7

Contd. on page 7



Printing date 15.12.2022 Version number 2 Revision: 01.12.2022

Trade name: Original ATE Brake Fluid SUPER DOT 5.1

	(Contd. of page 6)
110-97-4 1,1'	-iminodipropan-2-ol
EC50 (static)	>100 mg/l (Algae) (72 h)
	>100 mg/l (daphnia) (92/69/EWG 48 h)
LC50 (static)	>100 mg/L (fish) (OECD 203 96 h)
111-46-6 2,2'	oxybisethanol
EC50	>100 mg/l (Algae)
	>100 mg/l (daphnia) (DIN 38412 T.11)
LC50	>100 mg/L (fish) (96 h)
111-77-3 2-(2	-methoxyethoxy)ethanol
EC50	>100 mg/l (Algae)
	>100 mg/l (daphnia)
LC50 (static)	>100 mg/L (fish)

- 12.2 Persistence and degradability The single components are easily eliminable from water.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Disposal should be based on the relevant state and local laws and regulations, the disposal process should avoid pollution of the environment.

Recommendation

After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

European	European waste catalogue		
16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST		
16 01 00	end-of-life vehicles from different means of transport (including off-road machinery) and wastes from dismantling of end-of-life vehicles and vehicle maintenance (except 13, 14, 16 06 and 16 08)		
16 01 13*	brake fluids		

Uncleaned packaging:

Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTIO	N 14:	Transpor	t info	ormat	ion
--------	-------	----------	--------	-------	-----

14.1 UN	number or	ID number
ADD IN	IDC IATA	

ADR, IMDG, IATA Void

(Contd. on page 8)



Printing date 15.12.2022 Version number 2 Revision: 01.12.2022

Trade name: Original ATE Brake Fluid SUPER DOT 5.1

		(Contd. of page
14.2 UN proper shipping name ADR, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk accordi	ing to	
IMO instruments	Not applicable.	
UN "Model Regulation":	Void	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 54

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients are listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients are listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients are listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients are listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients are listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients are listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.

(Contd. on page 9)



Printing date 15.12.2022 Version number 2 Revision: 01.12.2022

Trade name: Original ATE Brake Fluid SUPER DOT 5.1

(Contd. of page 8)

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

Recommended restriction of use For industrial or professional purposes only.

Department issuing SDS:

Gefahrstoffmanagement Konzern ate.sicherheit@contiautomotive.com Date of previous version: 01.05.2020

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity - Category 2

Sources

http://echa.europa.eu/information-on-chemicals/cl-inventory

http://echa.europa.eu/web/guest/information-on-chemicals/registered-substances

http://www.reach-clp-biozid-helpdesk.de/de/Downloads/CLP-VO/CLP_VO_Anhang_VI_Tabelle_3_2.pdf http://www.safeworkaustralia.gov.au/

* Data compared to the previous version altered.

IE -