



Safety data sheet according to UK REACH

Printing date 18.05.2026

Version number 12.0

Revision: 01.11.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Original ATE Brake Fluid SL (DOT 4)

Article number: 03.9901-58xx.x / 7058xx

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture hydraulic liquid

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

AUMOVIO Aftermarket GmbH

Guerickestr. 7

60488 Frankfurt a. M.

Germany

Tel: +49-69-76031

Further information obtainable from:

Hazardous Substances Management Aftermarket, Central Materials Laboratory

ate.sicherheit@aumovio.com

1.4 Emergency telephone number:

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

INFOTRAC

+1-352-323-3500 (International)

+44 330 027 0156 (National)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Repr. 2 H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified according to the GB CLP regulation.

Hazard pictograms



GHS08

Signal word Warning

Hazard-determining components of labelling:

Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate

Hazard statements

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

(Contd. on page 2)



Safety data sheet according to UK REACH

Printing date 18.05.2026

Version number 12.0

Revision: 01.11.2025

Trade name: Original ATE Brake Fluid SL (DOT 4)

(Contd. of page 1)

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable**vPvB:** Not applicable

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 30989-05-0 EINECS: 250-418-4 Reg.nr.: 01-2119462824-33-XXXX	Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate Repr. 2, H361fd	≥30-<50%
EC number: 907-996-4 Reg.nr.: 01-2119531322-53-XXXX 01-2119475115-41-XXXX	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Eye Dam. 1, H318	≥10-<20%
CAS: 111-46-6 EINECS: 203-872-2 Reg.nr.: 01-2119457857-21-XXXX	2,2'-oxybisethanol Acute Tox. 4, H302	<10%
CAS: 110-97-4 EINECS: 203-820-9 Reg.nr.: 01-21194754444-34-XXXX	1,1'-Iminodipropan-2-ol Eye Irrit. 2, H319	<2%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures**General information:**

Take affected persons out of danger area.

Do not leave affected persons unattended.

Take off immediately all contaminated clothing.

After inhalation:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Seek medical treatment.

After skin contact:

If skin irritation occurs: Get medical advice/attention.

Immediately wash with water and soap and rinse thoroughly.

After eye contact:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Protect unharmed eye.

(Contd. on page 3)



Safety data sheet according to UK REACH

Printing date 18.05.2026

Version number 12.0

Revision: 01.11.2025

Trade name: Original ATE Brake Fluid SL (DOT 4)

(Contd. of page 2)

After swallowing:

Do NOT induce vomiting.
Rinse mouth thoroughly with water.
Call a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media
Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Nitrogen oxides (NO_x)

Boron oxides

During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters
Protective equipment:

Do not inhale explosion gases or combustion gases.
Wear self-contained respiratory protective device.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.
Do not allow to penetrate the ground/soil.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 4)



Safety data sheet according to UK REACH

Printing date 18.05.2026

Version number 12.0

Revision: 01.11.2025

Trade name: Original ATE Brake Fluid SL (DOT 4)

(Contd. of page 3)

Temperature class: T3

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Storage at room temperature.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from flammable substances.

Further information about storage conditions:

This product is hygroscopic.

Store in dry conditions.

Keep container tightly sealed.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Additional information about design of technical facilities: No further data; see section 7.

Ingredients with limit values that require monitoring at the workplace:

111-46-6 2,2'-oxybisethanol

WEL	Long-term value: 101 mg/m ³ , 23 ppm
-----	---

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Pregnant women should strictly avoid inhalation or skin contact.

Use skin protection cream for skin protection.

Respiratory protection:

In the case of vapour formation use a respirator with an approved filter.

Equipment should conform to EN 14387.

If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a short period of time.

filter ABEK-P2

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

Butyl caoutchouc (butyl rubber): minimum breakthrough time 480 min; minimum layer thickness: 0.7 mm

NBR (nitrile rubber): minimum breakthrough time 30 min; minimum layer thickness: 0.4 mm

Eye protection: Safety glasses

Body protection: Protective work clothing

Limitation and supervision of exposure into the environment

See section 6 and 7. No additional measures necessary.

Risk management measures

Ensure that activities are executed by specialists or authorised personnel only.

Use at industrial site in closed process with occasional controlled exposure or processes with equivalent containment conditions:

(Contd. on page 5)



Safety data sheet according to UK REACH

Printing date 18.05.2026

Version number 12.0

Revision: 01.11.2025

Trade name: Original ATE Brake Fluid SL (DOT 4)

(Contd. of page 4)

3 to 5 air changes per hour (90 % effectiveness) - basic standard of general ventilation
 maximum 8 h exposure duration per day
 maximum 40 °C process temperature
 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
 5 to 10 air changes per hour (90 % effectiveness) - good standard of controlled ventilation
 maximum 1 h exposure duration per day
 maximum 40 °C process temperature
 Use of functional fluids in small devices:
 5 to 10 air changes per hour (80 % effectiveness) - good standard of controlled ventilation
 maximum 8 h exposure duration per day
 maximum 40 °C process temperature
 Supervision in place to check that the risk management measures installed are being used correctly and operation conditions followed.
 Ensure control measures are regularly inspected and maintained.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Fluid
Colour:	Yellow
Odour:	Characteristic
Odour threshold:	Not determined

pH-value at 20 °C: 8.5 (50%) (FMVSS 116)

Change in condition

Melting point/freezing point: <-70 °C (DIN 51583)
 Initial boiling point and boiling range: >260 °C (FMVSS 116)

Flash point: 139 °C (ASTM D 7094)
 (closed cup)

Flammability: Not applicable

Auto-ignition temperature: >200 °C (DIN 51794)

Decomposition temperature: ca. 360 °C (DSC)

Ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

Explosion limits:

Lower: 1.5 Vol %
 Upper: Not determined

Vapour pressure at 20 °C: <1 hPa

Density at 20 °C: 1.06 g/cm³ (DIN 51757)

Relative density: Not determined

Vapour density: Not determined

Evaporation rate: Not determined

water: Fully miscible.

Partition coefficient: n-octanol/water: Not determined

(Contd. on page 6)

GB



Safety data sheet according to UK REACH

Printing date 18.05.2026

Version number 12.0

Revision: 01.11.2025

Trade name: Original ATE Brake Fluid SL (DOT 4)

(Contd. of page 5)

Viscosity:**Dynamic:**

Not determined

Kinematic at 20 °C:15-17 mm²/s (FMVSS 116)**9.2 Other information**

No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.**10.2 Chemical stability****Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.**10.4 Conditions to avoid** No further relevant information available.**10.5 Incompatible materials:** No further relevant information available.**10.6 Hazardous decomposition products:**

Carbon monoxide and carbon dioxide

Nitrogen oxides (NO_x)

Boron oxides

Hydrocarbons

SECTION 11: Toxicological information

11.1 Information on toxicological effects**Acute toxicity** Based on available data, the classification criteria are not met.**LD/LC50 values relevant for classification:****30989-05-0 Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate**

Oral LD50 >2,000 mg/kg (rat) (OECD 401)

Dermal LD50 >2,000 mg/kg (rat) (OECD 402)

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Oral LD50 >5,000 mg/kg (rat)

Dermal LD50 >3,000 mg/kg (rabbit)

111-46-6 2,2'-oxybisethanol

Oral LD50 >5,000 mg/kg (rat)

Dermal LD50 >5,000 mg/kg (rabbit)

110-97-4 1,1'-Iminodipropen-2-ol

Oral LD50 >2,000 mg/kg (rat) (OECD 401)

Dermal LD50 >5,000 mg/kg (rabbit)

Primary irritant effect:**Skin corrosion/irritation** Based on available data, the classification criteria are not met.**Serious eye damage/irritation** Based on available data, the classification criteria are not met.**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.**Additional toxicological information:****CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)****Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Suspected of damaging fertility. Suspected of damaging the unborn child.**STOT-single exposure** Based on available data, the classification criteria are not met.

(Contd. on page 7)



Safety data sheet according to UK REACH

Printing date 18.05.2026

Version number 12.0

Revision: 01.11.2025

Trade name: Original ATE Brake Fluid SL (DOT 4)

(Contd. of page 6)

STOT-repeated exposure Based on available data, the classification criteria are not met.**Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

EC50	6.25 mg/l (bacteria)
	250-350 mg/l (fish) (DIN 38412 96 h)

30989-05-0 Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate

EC50	>100 mg/l (algae) (72 h)
	>100 mg/l (daphnia) (48 h)
LC50	>100 mg/L (fish) (96 h)

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

EC50	>100 mg/l (algae)
LC50	>100 mg/L (daphnia)
	>100 mg/L (fish) (DIN 38412 96 h)

111-46-6 2,2'-oxybisethanol

EC50	>100 mg/l (algae)
	>100 mg/l (daphnia) (DIN 38412 T.11)
LC50	>100 mg/L (fish) (96 h)

110-97-4 1,1'-Iminodipropan-2-ol

EC50 (static)	>100 mg/l (algae) (72 h)
	>100 mg/l (daphnia) (92/69/EWG 48 h)
LC50 (static)	>100 mg/L (fish) (OECD 203 96 h)

12.2 Persistence and degradability No further relevant information available.**Other information:** The product is easily biodegradable.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow product to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable**vPvB:** Not applicable**12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Disposal should be based on the relevant state and local laws and regulations, the disposal process should avoid pollution of the environment.

Recommendation

After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

(Contd. on page 8)



Safety data sheet according to UK REACH

Printing date 18.05.2026

Version number 12.0

Revision: 01.11.2025

Trade name: Original ATE Brake Fluid SL (DOT 4)

(Contd. of page 7)

Uncleaned packaging:**Recommendation:**

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA

Void

14.2 UN proper shipping name

ADR, IMDG, IATA

Void

14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class

Void

14.4 Packing group

ADR, IMDG, IATA

Void

14.5 Environmental hazards:

Not applicable

14.6 Special precautions for user

Not applicable

**14.7 Transport in bulk according to Annex II of
Marpol and the IBC Code**

Not applicable

UN "Model Regulation":

Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**Poisons Act****Regulated explosives precursors**

None of the ingredients are listed.

Regulated poisons

None of the ingredients are listed.

Reportable explosives precursors

None of the ingredients are listed.

Reportable poisons

None of the ingredients are listed.

National regulations:**Information about limitation of use:**

Employment restrictions concerning pregnant and lactating women must be observed.

Other regulations, limitations and prohibitive regulations**Substances of very high concern (SVHC) according to UK REACH**

None of the ingredients are listed.

(Contd. on page 9)

GB



Safety data sheet according to UK REACH

Printing date 18.05.2026

Version number 12.0

Revision: 01.11.2025

Trade name: Original ATE Brake Fluid SL (DOT 4)

(Contd. of page 8)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

It is the sole responsibility of the importer or distributor to identify and comply with all legal requirements necessary for the lawful placing of chemical products on the market in the respective target countries.

Relevant phrases

H302 Harmful if swallowed.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

Recommended restriction of use For industrial or professional purposes only.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS:

Hazardous Substances Management Aftermarket

ate.sicherheit@aumovio.com

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

*** Data compared to the previous version altered.**